



# Instructions

## Compact Lock Jig

Technical Support Helpline - 0191 2597876

[www.worktopjigs.com](http://www.worktopjigs.com)

### UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park,  
Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: [sales@unika.co.uk](mailto:sales@unika.co.uk) [www.unika.co.uk](http://www.unika.co.uk)



The mark of responsible forestry



# **LOCK CUTOUT JIG**

The Lock Jig is designed to help the routing out of door edges to accommodate lock bodies and face plates. The jig is self-centring when clamped to the door. Before use the jig must be assembled. Insert each of the F shaped clamps through the holes in the face at each end of the jig and fix them in place with the retaining butterfly bolts.

Whether you have used a jig or not previously, please take time to read through this booklet carefully. We have designed this lock jig to be as easily as possible to use. We recommend that you practice with the design and with the jig on some suitable off-cuts prior to working on the first installation.

A 16mm guide bush and a 12.7mm (1/2") straight cutter are used.

## **SAFETY FIRST**

- 1. Make sure all cables are clear of the router.**
- 2. Make sure the work piece is correctly supported.**
- 3. Always use protective goggles when using the router.**
- 4. Do not switch router on with blade touching the work piece.**
- 5. Never remove the router from the jig when it is switched on.**
- 6. Make sure there are no obstructions to the path of the router.**
- 7. READ INSTRUCTIONS CAREFULLY BEFORE STARTING THE WORK.**

## **Using the Jig.**

1. Set the door with the edge to be routed facing up.
2. Mark the centre point of the lock position and draw a line through this point across the width of the door edge.
3. Loosen slightly the butterfly bolts on the jig, set the two clamp handles at right angles to the jig then place the jig on the edge of the door.
4. Select the correct size insert for the lock that is to be fitted and place into recess on jig face. Place jig so that engraved lines match up with line marked on the edge of the door.
5. Move the clamp handles to hold the jig firmly on the door edge. This will centre the cut out vertically on the door edge. Again check that the centre marks are aligned then tighten the butterfly bolts.
6. Set the router at the required depth.

## **CUTTING**

1. Always work clockwise.
2. Start in the centre of the area to be cut and work towards the edge.
3. Never cut more than 10 mm depth at one cut.
4. Increase depth by 10 mm or less until aperture is cut.
5. Always switch router off and allow to stop before removing from the jig.
6. Never remove the router from the jig when it is switched on.

# Worktop Installation Essentials

Unika ColorFill is the first sealant to be designed specifically for the installation of mitred worktop joints.

ColorFill performs three tasks: It bonds the joint together, it seals the joint against water and domestic detergents and it is exactly colour matched to the worktop so making the finished joint almost invisible.

In addition to joints ColorFill will repair scratches and chips in laminate and melamine surfaces.

Find your ColorFill now at [www.colorfill.co.uk](http://www.colorfill.co.uk)



ColorFill Solid Surface Adhesive is a revolutionary two component Methyl Methacrylate which will provide a colour matched seamless look for Solid Surface Worktops.

It can be used on Solid Surface and Composite Worktops made from Acrylic and Acrylic and Polyester blends for example – Corian, HI-MAC'S, Slab Tech, Earthstone, Avonite

EasiBolt will join two mitred worktops together

The Easibolt holder will keep the bolt in place on the underside of the worktop and leave both hands free for tightening or levelling

EasiBolt is a patented product



TopSeal is a Colour matched Backsplash and Upstand Sealant. High Strength/Waterproof/Flexible It Bonds and Seals at the same time.

TopSeal adheres to all surfaces Granite, Quartz, Laminate, Stainless Steel, Glass and many others.

TopSeal is an excellent gap filler and has little shrinkage. Waterproof and flexible once cured.

10 – 15 minutes open time Excellent bond strength. Use to secure Upstands and Backsplashes in place.

MitrePen is a quick and strong system for joining cornice, pelmet and plinth.

MitrePen is an environmentally friendly, precision marker that prevents the staining caused by overspray.

MitrePen is quick and clean and sets in 10 seconds

Use on: Cornice & Profile Mitre Joints, Melamine end strips, door trims, picture frames, mdf, skirting joints etc.



Gloss Surface Cleaner is a ready to use foam cleaner produces a smear free finish on gloss cupboard doors specially designed to remove dust, light dirt and water marks.

Use on glass, mirrors and chrome surfaces. Cleans and polishes in one easy application.

Professional grade cleaner that will reduce the rate of static pick up on a surface and so reduce the dust build up.

## UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park, Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: [sales@unika.co.uk](mailto:sales@unika.co.uk) [www.unika.co.uk](http://www.unika.co.uk)

